

IN THE CLAIMS

Please amend the claims as follows:

- Sub B1
- A1
1. (Original) A device, comprising:  
circuitry for communicating with a medical device that is adapted for acquiring data regarding cardiac events occurring at two or more sites; and  
a display for providing a histogram of the data as two or more statistical distributions for the two or more sites, wherein the histogram includes both a right ventricular cardiac event distribution and a left ventricular cardiac event distribution.
  2. (Original) The device of claim 1, wherein the data includes both sensed intrinsic cardiac events and paced cardiac events.
  3. (Original) The device of claim 1, wherein the two or more sites include a first site and a second site in a first cardiac chamber.
  4. (Original) The device of claim 1, wherein the two or more sites include a first site and a second site in a first cardiac chamber, and further include a third site in a second cardiac chamber.
  5. (Original) The device of claim 1, further including a second histogram to provide a statistical distribution for atrial events.
  6. (Original) The device of claim 1, wherein the histogram comprises a plurality of histogram bins for the two or more statistical distributions, each of the histogram bins including:  
a portion of the right ventricular cardiac event distribution; and  
a portion of the left ventricular cardiac event distribution.

7. (Original) The device of claim 6, wherein the portion of the right ventricular cardiac event distribution is adjacent to the portion of the left ventricular cardiac event distribution in each of the histogram bins.

8. (Original) The device of claim 6, wherein the histogram further comprises a histogram axis extending through each of the histogram bins, and wherein the portion of the right ventricular cardiac event distribution and the portion of the left ventricular cardiac event distribution are on opposing sides of the histogram axis in each of the histogram bins.

9. (Original) The device of claim 6, wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are distinguished using different colors.

10. (Original) The device of claim 6, wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution each include both a sensed intrinsic cardiac event distribution and a paced cardiac event distribution.

11. (Original) The device of claim 10, wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are formed by summing the sensed intrinsic cardiac event distribution with the paced cardiac event distribution.

12. (Original) The device of claim 10, wherein the sensed intrinsic cardiac event distribution and the paced cardiac event distribution are distinguished using different fillings.

13. (Currently Amended) The device of claim 1, wherein:  
the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are determined by dividing an event count in bin by a denominator;  
the denominator is the sum of a total right ventricular sense (RVS) RVS count, a total right ventricular pace (RVP) RVP count, and a total left ventricular pace (LVP) LVP count; and  
the LVP count includes only left ventricular pacing events in which no right ventricular pace is delivered for a corresponding cardiac cycle.

- Sub  
B1
14. (Original) The device of claim 1, wherein the medical device is a pacemaker.
15. (Original) The device of claim 1, wherein the medical device is a defibrillator.
16. (Original) The device of claim 1, wherein the histogram includes programmed tachy zone rate thresholds.
17. (Currently Amended) The device of claim 1, wherein the ~~programmer displays the data using~~ display includes a monitor for displaying the histogram.
18. (Currently Amended) The device of claim 1, wherein the ~~programmer displays the data using~~ display includes a printer for printing a display of the histogram.
19. (Original) A device, comprising:
- circuitry for communicating with a medical device that is adapted for acquiring data regarding cardiac events occurring at two or more sites;
  - a display for providing a histogram of the data as statistical distributions for the two or more sites;
  - wherein the two or more sites include a first site in a left ventricle and a second site in a right ventricle;
  - wherein the histogram comprises a plurality of histogram bins for the statistical distributions;
  - wherein the histogram includes both a right ventricular cardiac event distribution and a left ventricular cardiac event distribution;
  - wherein the right ventricular cardiac event distribution is adjacent to the left ventricular cardiac event distribution; and
  - wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution each include both a sensed intrinsic cardiac event distribution and a paced cardiac event distribution.

20. (Original) The device of claim 19, further comprising a second histogram to provide a statistical distribution for atrial events.

21. (Original) A programmer device, comprising:

Sub  
B1  
a  
circuitry for communicating with a medical device that is adapted for acquiring data regarding cardiac events occurring at two or more sites; and a display for providing a histogram of the data as two or more statistical distributions for the two or more sites, wherein the statistical distributions are selected from the set consisting of:

at least one left ventricle statistical distribution and at least one right ventricle statistical distribution;

at least two left ventricle statistical distributions;

at least two right ventricle statistical distributions;

at least one left atrium statistical distribution and at least one right atrium statistical distribution;

at least two left atrium statistical distributions; and

at least two right atrium statistical distributions.

22. (Original) The programmer device of claim 21, wherein:

a cardiac event distribution is determined by dividing an event count in bin by a denominator;

the denominator is the sum of a total primary site sense count, a total primary site pace count, and a total secondary site pace count; and

the secondary pace count includes only secondary pacing events in which no primary pace is delivered for a corresponding cardiac cycle.

23. (Currently Amended) The programmer device of claim 22, wherein:

the two or more sites include at least one left ventricle site and at least one right ventricle site;

the primary site sense count is a right ventricular sense (RVS) RVS count;

the primary site pace count is a right ventricular pace (RVP) RVP count; and  
the secondary site pace count is a left ventricular pace (LVP) LVP count.

- Sub  
B1  
A
24. (Original) The programmer device of claim 21, wherein the data includes both sensed intrinsic cardiac events and paced events.
25. (Original) A programmer device, comprising:  
circuitry for communicating with a medical device that is adapted for acquiring data regarding cardiac events occurring at two or more sites; and  
a display for providing a histogram of the data as two or more statistical distributions for the two or more sites, wherein the statistical distributions are selected from the set consisting of:  
at least two statistical distributions in a first ventricle and at least one statistical distribution in a second ventricle; and  
at least two statistical distributions in a first atrium and at least one statistical distribution in a second atrium.
26. (Original) A method, comprising:  
acquiring data regarding cardiac events occurring at two or more sites; and  
displaying the data in a histogram as two or more statistical distributions for the two or more sites, wherein the histogram includes a right ventricular cardiac event distribution and a left ventricular cardiac event distribution.
27. (Currently Amended) The method of claim 26, wherein ~~providing~~ displaying the right ventricular cardiac event distribution and the left ventricular cardiac event distribution in the histogram comprises providing the right ventricular cardiac event distribution adjacent to the left ventricular cardiac event distribution in each of the histogram bins.
28. (Currently Amended) The method of claim 26, wherein:  
the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are determined by dividing an event count in bin by a denominator;

the denominator is the sum of a total right ventricular sense (RVS) RVS count, a total right ventricular pace (RVP) RVP count, and a total left ventricular pace (LVP) LVP count; and

the LVP count includes only left ventricular pacing events in which no right ventricular pace is delivered for a corresponding cardiac cycle.

29. (Original) A method, comprising:

acquiring data regarding both paced and sensed cardiac events occurring at a left ventricle and a right ventricle; and

providing a left ventricular cardiac event distribution adjacent to a right ventricular cardiac event distribution in a histogram having a plurality of histogram bins, wherein the left ventricular cardiac event distribution includes both paced and sensed cardiac event distributions, and the right ventricular cardiac event distribution includes both paced and sensed cardiac event distributions.

30. (Original) The method of claim 29, further comprising providing an atrial event distribution in a second histogram.

31. (Currently Amended) A computer-readable medium encoded with computer-readable instructions, when executed the instructions create a histogram for displaying data regarding cardiac events as two or more statistical distributions, the histogram comprising:

a plurality of histogram bins for the two or more statistical distributions, each of the histogram bins including:

a portion of a right ventricular cardiac event distribution; and

a portion of a left ventricular cardiac event distribution;

32. (Currently Amended) The histogram computer-readable medium of claim 31, wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are distinguished using different colors.

Sub  
B1  
a1

33. (Currently Amended) The ~~histogram~~ computer-readable medium of claim 31, wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution each include both a sensed intrinsic cardiac event distribution and a paced cardiac event distribution.

34. (Currently Amended) The ~~histogram~~ computer-readable medium of claim 31, wherein the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are formed by summing the sensed intrinsic cardiac event distribution with the paced cardiac event distribution.

35. (Currently Amended) The ~~histogram~~ computer-readable medium of claim 31, wherein the sensed intrinsic cardiac event distribution and the paced cardiac event distribution are distinguished using different fillings.

36. (Currently Amended) The ~~histogram~~ computer-readable medium of claim 31, wherein the right ventricular cardiac event distribution is adjacent to the left ventricular cardiac event distribution.

37. (Currently Amended) The ~~histogram~~ computer-readable medium of claim 31, further comprising a histogram axis extending through each of the histogram bins, wherein the portion of the right ventricular cardiac event distribution and the portion of the left ventricular cardiac event distribution are on opposing sides of the histogram axis.

38. (Currently Amended) The ~~histogram~~ computer-readable medium of claim 31, wherein:  
the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are determined by dividing an event count in bin by a denominator;  
the denominator is the sum of a total right ventricular sense (RVS) ~~RVS~~ count, a total right ventricular pace (RVP) ~~RVP~~ count, and a total left ventricular pace (LVP) ~~LVP~~ count; and  
the LVP count includes only left ventricular pacing events in which no right ventricular pace is delivered for a corresponding cardiac cycle.

39. (Original) A computer-readable medium encoded with a software program for displaying cardiac event data, the software program executing the following:

retrieving data regarding cardiac events occurring at two or more sites; and

displaying the data in a histogram as two or more statistical distributions for the two or more sites, wherein the histogram includes a right ventricular cardiac event distribution and a left ventricular cardiac event distribution.

40. (Currently Amended) The computer-readable medium of claim ~~35~~ 39, wherein:

the right ventricular cardiac event distribution and the left ventricular cardiac event distribution are determined by dividing an event count in bin by a denominator;

the denominator is the sum of a total right ventricular sense (RVS) ~~RVS~~ count, a total right ventricular pace (RVP) ~~RVP~~ count, and a total left ventricular pace (LVP) ~~LVP~~ count; and

the LVP count includes only left ventricular pacing events in which no right ventricular pace is delivered for a corresponding cardiac cycle.

41. (New) A device, comprising:

a processor;

communication circuitry to communicate with the processor and with a medical device that is adapted for acquiring data regarding cardiac events occurring at two or more sites;

a display to communicate with the processor; and

a memory to communicate with the processor, the memory being encoded with a software program that is executable by the processor to:

retrieve data from the communication circuitry regarding the cardiac events occurring at the two or more sites;

form a statistical distribution for each of the two or more sites; and

display the statistical distribution for each of the two or more sites in a histogram,

the histogram including a plurality of histogram bins, wherein each histogram bin includes a representation for at least a portion of the statistical distribution for each of the two or more sites.



42. (New) The device of claim 41, wherein each of the histogram bins includes:  
a representation for at least a portion of a right ventricular cardiac event distribution; and  
a representation for at least a portion of a left ventricular cardiac event distribution.
43. (New) The device of claim 42, wherein the representation for at least a portion of a right ventricular cardiac event distribution is adjacent to the representation for at least a portion of a left ventricular cardiac event distribution.
44. (New) The device of claim 42, wherein the histogram further comprises a histogram axis extending through each of the histogram bins, and wherein the representation for at least a portion of a right ventricular cardiac event distribution and the representation for at least a portion of a left ventricular cardiac event distribution are on opposing sides of the histogram axis in each of the histogram bins.